



www.systemthree.com

TECHNICAL DATA SHEET
SPAR URETHANE VARNISH

System Three Spar Urethane Varnish is a high gloss, high-solids, V.O.C. compliant finish designed for marine and exterior wood surfaces such as boats, patio furniture, doors or any surface where a clear gloss is desired.

SURFACE PREPARATION: Wood should be free of dust, grease, oil, wax, and any other foreign matter. Sanding should be done prior to and between coats both on new and old surfaces.

APPLICATION: For best results, use a high-quality, natural bristle brush. OVER CURED EPOXY: Sand epoxy surface to a clean, dry surface and apply with no thinning. NEW WORK(BARE WOOD): Apply two or three coats full strength as required for protection. OLD WORK: If previously varnished surface is in good condition, sand and varnish.

STAINING: Use a high-quality wiping stain intended for wood. Allow to cure thoroughly, according to the manufacturer's instructions. Test for adhesion after staining.

COVERAGE: 350-400 ft² per gallon

DRY TIME*: DUST FREE: 2 to 4 hours
RECOAT: 12 to 24 hours
DRY HARD: 24-48 hours

*Dry times will vary with temperature, humidity, and ventilation.

THINNING: None required. Thinning is not recommended

CLEAN UP: Mineral Spirits

V.O.C. Content: 450 grams/liter (3.75 lb/gal)

For health and safety information concerning this product, please refer to the Material Safety Data Sheet for Spar Urethane Varnish.

The information contained herein is based on the data available to us and is believed to be correct. However, System Three Resins, Inc. makes no warranty, expressed or implied, regarding the accuracy of these data or the results to be obtained from the use thereof.